

3M™ Automotive Window Film

FXPM 55



Technical Data

*Will not interfere with cellular phones, GPS, or satellite radio signals.

Product Benefits

- Metal-free design with no electronic interference*
- Much less reflectivity than traditional window films
- Good heat rejection capability
- Up to 99% UV protection

Product Performance & Technical Data

FXPM 55				
	Single Pane		Single Pane Auto75	
Film	1/4" Clear	FXPM 55	1/4" Auto75	FXPM 55
Solar Heat Gain Coefficient	0.82	0.69	0.59	0.51
Visible Light Transmitted	89%	58%	75%	49%
Visible Light Reflected Interior	9%	7%	7%	7%
Visible Light Reflected Exterior	8%	7%	7%	6%
U Value	1.03	1.05	1.02	1.03
UV Block	38%	96%	NA	99.9%
Total Solar Energy Rejected	19%	31%	41%	49%
Glare Reduction	NA	34%	NA	35%
Heat Loss Reduction	NA	0%	NA	0%
Solar Heat Reduction	NA	15%	NA	14%

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.



Renewable Energy Division

St. Paul, MN 55144-1000

1-866-499-8857

www.3M.com/windowfilm

3M is a trademark of 3M Company.

© 3M 2016. All rights reserved.