Product Features and Benefits

3M™ Safety & Security Impact Protection Attachment (IPA) Sealant is a liquid caulk edge retention system designed to hold the 3M Safety and Security Window film in place to help provide additional impact protection from a variety of sources including bomb blasts, extreme weather and forced entry events. The 3M Impact Protection System (film and IPA) helps protect against personal injury from flying glass.

- Excellent tear, elongation and tensile strength
- Anchors the filmed glass to the window frame
- Available in Black, White and Gray

Performance Data

Property	Test Method	Values w/ Units
Curing Time (25°C (77°F), 50% RH)		7-14 Days
Full Adhesion	ASTM C639	> 14 Days
Tack Free Time (25°C (77°F), 50% RH)	ASTM C679	60 Minutes
Flow, Sag or Slump	ASTM C639	0.1 Inches
Working Time (25°C (77°F), 50% RH)		10-20 Minutes
Specific Gravity		1.34
VOC Content		30 gm/l
As Cured – After 7 Days at 25°C (77°F), 50% RH		
Durometer Hardness, Shore A	ASTM D2240	40 Points
Peel Strength	ASTM C794	40 ppi
Tear Strength, Die B	ASTM D624	49 ppi
As Cured- After 21 days at 25° (77°F), 50% RH		
Ultimate Tensile Strength	ASTM D412	170 Psi
Joint Movement Capability	ASTM C719	± 50%

Shelf life of 18 months from manufacture date if stored below 90°F.

IMPORTANT NOTICE: This product is **not approved** in the State of Florida for use as hurricane, windstorm, or impact protection from windborne debris from a hurricane or windstorm. In compliance with Florida Statute 553.842, this product may not be advertised, sold, offered, provided, distributed, or marketed in the State of Florida as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm. The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.

Commercial Solutions Division



3M™ Impact Protection Attachment Systems

3M™ Impact Protection Attachment (IPA) Sealant

Health and Safety

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to <u>3M.com/SDS</u>, or by mail or in case of an emergency, call 1-888-364-3577 or 1-651-737-6501.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (*e.g.*, OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

IMPORTANT NOTICE: This product is **not approved** in the State of Florida for use as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm. In compliance with Florida Statute 553.842, this product may not be advertised, sold, offered, provided, distributed, or marketed in the State of Florida as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm. The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.

Commercial Solutions Division

3M Center, Building 220-12E-04 St. Paul, MN 55144. 3M.com/windowfilm © 3M 2020. All rights reserved. 3M is a trademark of 3M. Used under license in Canada. All other trademarks are property of their respective owners. Revision B, September 2020. Please recycle.

