

3M™ Sun Control Window Film Prestige 20


Clearly superior.

Benefits

- ▶ High visible light transmission providing excellent aesthetics
- ▶ Up to 97% infrared rejection providing energy savings and enhanced comfort*
- ▶ Low interior and exterior reflectivity enhances views while maintaining exterior appearance
- ▶ Non-metalized film with no signal interference and no chance for corrosion
- ▶ Helps extend the life of furnishings by significantly reducing harmful UV rays, the largest cause of fading
- ▶ The Prestige Series can become carbon negative in as short as 6 months from install**
- ▶ Comprehensive warranty from 3M

*For wavelengths from 900–1000nm

**Based on emission calculations performed in compliance with the GHG Protocol Product Life Cycle Accounting and Reporting Standard (2011), third party assured by Quality Associates incorporated, and energy savings calculation completed by CONSOL Energy. Contact 3M for details.



3M is a trademark of 3M Company. Used under license by 3M subsidiaries and affiliates. Please recycle. Printed in the U.S.A. © 3M 2016. All rights reserved. 98-0150-1138-4



Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If the 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

LEED Certification

Window films may be used toward the following LEED credits:

◀ EA-1	◀ EQ-7.1	◀ MR 5.1-5.2	◀ EQ-7.2
◀ SS-8	◀ EQ-7.1	◀ MR 1.1-1.2	◀ EQ-8.1-8.2

Glass Type (All 1/4")	Film Type	Reflected (Interior)	Reflected (Exterior)	Transmitted	Normal 60 degree angle	Solar Heat Gain Coefficient (G Value)	Solar Heat		Visible Light			
							U Value	btu/w/ft ² /m ² k				
Double Tinted	PR20	5%	8%	11%	61%	0.39	0.47	2.70	24%	99.9%	76%	0.3
Double Clear	PR20	5%	13%	19%	50%	0.51	0.47	2.70	28%	99.9%	77%	0.4
Tinted	PR20	5%	5%	13%	64%	0.36	1.03	5.82	43%	99.9%	76%	0.4
Clear	PR20	5%	6%	21%	62%	0.38	1.03	5.82	54%	99.9%	76%	0.6

Product Performance and Technical Data