



Sun Control Window Films


Performance Results:

Visible Light Transmitted	33%
Total Solar Energy Rejected	61%
UV Light Rejected	99%
Glare Reduction	63%
Visible Light Reflected Interior	19%
Visible Light Reflected Exterior	29%



Affinity 30

*Enhancing light
as only 3M can*



Sample Area Diecut

Affinity 30 Benefits:

- High heat rejection provides energy savings and improved comfort
- Reduces fading and helps to protect furnishings
- Lower interior and exterior reflectivity
- Reduces glare and eye discomfort
- Comprehensive 3M manufacturer's warranty
- Increases personal safety from flying glass

Glass Type (All 1/4")	Single Pane Clear	Single Pane Tinted	Double Pane Clear	Double Pane Tinted
Visible Light Transmitted	33%	20%	30%	18%
Total Solar Energy Rejected	61%	63%	54%	64%
UV Light Rejected	99%	99%	99%	99%
Glare Reduction	63%	62%	62%	62%
Visible Light Reflected Int.	19%	19%	20%	20%
Visible Light Reflected Ext.	29%	14%	32%	15%
Shading Coefficient	0.45	0.42	0.53	0.41
Emissivity	0.67	0.67	0.67	0.67
U Value	0.94	0.94	0.45	0.45
Solar Heat Reduction	52%	42%	35%	31%

3M Building Safety Solutions Department
 3M Center, Building 223-2S-24
 St. Paul, MN 55144-1000
 Printed in U.S.A. © 3M 2006 70-0709-0166-8