

### Product Benefits

- Metal-free design with no electronic interference
- 3M patented Infuse Technology provides better durability, color retention and fade resistance
- Much less reflectivity than traditional window films
- Good heat rejection capability
- Up to 99+% UV protection

### Product Performance & Technical Data

	Product	VLT	Visible Reflection Exterior	Visible Reflection Interior	UV Block	TSER	Glare Reduction
<b>6mm Clear*</b>	<b>6mm Clear</b>	<b>89%</b>	<b>9%</b>	<b>8%</b>	<b>34.0%</b>	<b>19%</b>	<b>NA</b>
	<b>OB 5</b>	<b>8%</b>	<b>5%</b>	<b>5%</b>	<b>99.8%</b>	<b>44%</b>	<b>91%</b>
	<b>OB 15</b>	<b>19%</b>	<b>5%</b>	<b>5%</b>	<b>99.7%</b>	<b>40%</b>	<b>79%</b>
	<b>OB 25</b>	<b>27%</b>	<b>6%</b>	<b>5%</b>	<b>99.6%</b>	<b>38%</b>	<b>69%</b>
	<b>OB 30</b>	<b>34%</b>	<b>6%</b>	<b>5%</b>	<b>99.6%</b>	<b>36%</b>	<b>62%</b>
	<b>OB 35</b>	<b>39%</b>	<b>6%</b>	<b>5%</b>	<b>99.6%</b>	<b>35%</b>	<b>56%</b>
	<b>OB 40</b>	<b>43%</b>	<b>6%</b>	<b>5%</b>	<b>99.5%</b>	<b>34%</b>	<b>52%</b>
	<b>OB 50</b>	<b>52%</b>	<b>7%</b>	<b>6%</b>	<b>99.4%</b>	<b>31%</b>	<b>41%</b>
	<b>OB 80</b>	<b>78%</b>	<b>8%</b>	<b>8%</b>	<b>99.3%</b>	<b>23%</b>	<b>12%</b>
<b>6mm Auto75**</b>	<b>6mm Auto75</b>	<b>73%</b>	<b>7%</b>	<b>7%</b>	<b>78.0%</b>	<b>42%</b>	<b>NA</b>
	<b>OB 5</b>	<b>7%</b>	<b>5%</b>	<b>5%</b>	<b>99.9%</b>	<b>59%</b>	<b>91%</b>
	<b>OB 15</b>	<b>16%</b>	<b>5%</b>	<b>5%</b>	<b>99.9%</b>	<b>57%</b>	<b>79%</b>
	<b>OB 25</b>	<b>22%</b>	<b>5%</b>	<b>5%</b>	<b>99.8%</b>	<b>55%</b>	<b>70%</b>
	<b>OB 30</b>	<b>28%</b>	<b>5%</b>	<b>5%</b>	<b>99.8%</b>	<b>54%</b>	<b>63%</b>
	<b>OB 35</b>	<b>32%</b>	<b>5%</b>	<b>5%</b>	<b>99.8%</b>	<b>53%</b>	<b>57%</b>
	<b>OB 40</b>	<b>35%</b>	<b>5%</b>	<b>5%</b>	<b>99.8%</b>	<b>52%</b>	<b>53%</b>
	<b>OB 50</b>	<b>43%</b>	<b>6%</b>	<b>6%</b>	<b>99.8%</b>	<b>50%</b>	<b>43%</b>
	<b>OB 80</b>	<b>64%</b>	<b>7%</b>	<b>7%</b>	<b>99.7%</b>	<b>45%</b>	<b>15%</b>

\* Data is comparable to current auto industry method using a clear 89% VLT glass, and testing is in accordance to ANSI/NFRC 200 Procedure.

\*\* Data should be used as a reference tool for worst case scenario of net VLT on automotive clear glass of 73% VLT.

### Health and Safety



#### CAUTION

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to [3M.com/SDS](http://3M.com/SDS), or by mail or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.



### Technical Information

Technical information and data, recommendations, and other statements provided by 3M are based on information, tests, or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed. Such technical information and data are intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. The typical values shown should not be used for the purpose of specification limits. If you have questions about this Product, contact the Technical Service helpline at 1-866-499-8857.

### Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

### Warranty

3M and the Authorized Automotive Window Film Dealer (collectively referred to as "Seller" herein) warrant that as long as you own your vehicle, 3M™ Automotive Window Film Obsidian Series will:

1. Maintain Solar Reflective properties without cracking or crazing.
2. Maintain Adhesion without blistering, bubbling or delaminating from the glass.
3. Maintain film color.

3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

### Limited Remedy

If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

### No Extension of Warranty

In the case of an approved warranty claim, the replacement Product will carry only the remaining term of the original warranty period.

### Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.