

Product Benefits

- Good heat rejection capability
- Less reflectivity than traditional window films
- Metal-free design with no electronic interference
 - Will not interfere with cell phones, GPS systems or satellite radio
- Up to 99% UV Protection

Product Performance & Technical Data

Auto 75*	Film	Visible Light Transmittance	Visible Light Reflectance Exterior	Visible Light Reflectance Interior	UV Block	Total Solar Energy Rejected	Glare Reduction	Infrared Rejection****	Infrared Energy Rejection*****
	Auto 75 Glass	73%	7%	7%	67%	42%	NA	NA	NA
	FXPM 5	5%	5%	5%	99%	59%	93%	21%	54%
	FXPM 15	14%	5%	5%	98%	58%	81%	22%	54%
	FXPM 25	20%	5%	5%	98%	56%	72%	22%	54%
	FXPM 30	27%	5%	5%	99%	55%	64%	22%	54%
	FXPM 35	33%	5%	5%	98%	53%	55%	22%	54%
	FXPM 40	37%	5%	5%	98%	52%	50%	21%	55%
	FXPM 55	48%	6%	6%	98%	49%	34%	19%	54%

6mm Clear**	Film	Visible Light Transmittance	Visible Light Reflectance Exterior	Visible Light Reflectance Interior	UV Block	Total Solar Energy Rejected	Glare Reduction	Infrared Rejection****	Infrared Energy Rejection*****
	Clear Glass	89%	9%	8%	34%	19%	NA	NA	NA
	FXPM 5	7%	5%	5%	99%	44%	92%	21%	28%
	FXPM 15	17%	5%	5%	96%	42%	81%	22%	27%
	FXPM 25	24%	5%	5%	96%	40%	73%	22%	27%
	FXPM 30	32%	6%	5%	97%	38%	64%	22%	29%
	FXPM 35	40%	6%	6%	96%	36%	55%	22%	28%
	FXPM 40	44%	6%	6%	96%	35%	50%	21%	29%
	FXPM 55	58%	7%	7%	96%	31%	34%	19%	29%

* Data should be used as a reference tool for net VLT on ¼” (6mm) thick, automotive green glass of 73% VLT, and testing is in accordance to ANSI/NFRC 200 Procedure.

** Data is comparable to current auto industry method using a clear 89% VLT glass, and testing is in accordance to ANSI/NFRC 200 Procedure.

***Will not interfere with cell phones, GPS systems or satellite radio.

****IRR - IR Rejected over 900 – 1,000 nm. Film with liner measurement

*****IRER – The percent of solar infrared energy rejection over the wavelength range from 780 – 2,500 nm. IRER takes into account the transmitted and absorbed IR energy that will be reradiated into a car. Film is applied to glass

Commercial Solutions Division

3M Center, Building 220-12E-04 St. Paul, MN 55144

3M.com/windowfilm

© 3M 2021. All rights reserved.

3M is a trademark of 3M. Used under license in Canada.

All other trademarks are property of their respective owners. Revision A, April 2021. Please recycle.



AIS

View the Article Information Sheet (AIS), document # 28-0414-4 for 3M FXPM Series at [3M.com/SDS](https://www.3m.com/SDS).

Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third-party intellectual property rights is granted or implied with this information. If you have questions about this Product, contact the Customer Service Department at 1-866-499-8857.

Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Commercial Solutions Division

3M Center, Building 220-12E-04 St. Paul, MN 55144
[3M.com/windowfilm](https://www.3m.com/windowfilm)

© 3M 2021. All rights reserved.

3M is a trademark of 3M. Used under license in Canada.

All other trademarks are property of their respective owners. Revision A, April 2021. Please recycle.

