

3M™ Scotchshield™ Safety & Security Window Film

Ultra Prestige 70



Tear-resistance and sun control

Benefits

- Combines the benefits of 3M™ Ultra Series with the benefits of 3M™ Prestige Series Window Film
- Micro-layered film designed for tear resistance and glass fragment retention
- Virtually clear (70% Visible Light Transmission) with solar heat rejection properties
- For application only to interior glass surfaces of windows and doors
- Low interior reflectivity offers enhanced views
- Engineered to help hold broken glass in place
- Helps prevent flying glass shards from harming occupants and damaging property
- Blocks up to 99% of the sun’s UV rays, the largest single cause of fading
- Product must be installed with the 3M™ Impact Protection Attachment (IPA) Sealant for all windstorm, break & entry, and explosion mitigation applications and for all spontaneous glass breakage applications on single pane tempered glass (product is not bulletproof and is not designed to stop intruders)
- Comprehensive warranty from 3M



All rights reserved. 98-0150-1070-9
Printed in the U.S.A. © 3M 2025.
and affiliates. Please recycle.
3M Company.
Used under license by 3M subsidiaries
3M and Scotchshield are trademarks of
3M.com/WindowFilm
St. Paul, MN 55144-1000
3M Center, Building 223-3N-30
Commercial Branding and Transportation



IMPORTANT: This is an overview of product features and benefits. Prior to product selection, always refer to the current 3M Technical Data Sheet and 3M Technical Specifications for more detailed product information. Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application. Failure to properly evaluate, select, and use a 3M product may result in injury, sickness, death, and/or harm to property. This product is not approved in the State of Florida for use as hurricane, windstorm, or impact protection from wind-borne debris from a hurricane or windstorm.

CAUTION: Although certain 3M™ Window Films help block a certain percentage of UVA and UVB radiation and may have received The Skin Cancer Foundation Seal of Recommendation, the efficacy of these films in protecting against skin cancer has not been tested by 3M and 3M™ WINDOW FILMS DO NOT PREVENT SKIN CANCER.

CAUTION: While 3M™ Window Films, when applied in accordance with 3M instructions, may help reduce the impact of flying glass shards under certain conditions and potentially delay intruders, **THESE FILMS DO NOT PREVENT PROPERTY DAMAGE, PERSONAL INJURY, OR DEATH. WINDOW FILMS ARE NOT BULLETPROOF AND NOT DESIGNED TO STOP INTRUDERS.**

IMPORTANT: This is an overview of product features. References to explosions or blasts apply only to commercial and non-educational government facility applications. Prior to product selection, always refer to the current 3M Technical Data Sheet for detailed product information.

Film Type	Ultra Prestige S70
Film Thickness	8 mil (0.22mm)
Construction	Micro-layered
Tear Resistance	1,150 lbs/in
Tensile Strength	26,300 psi (186 MPa)
Break Strength	200 lbs/in (956 N/25mm)
Elongation at Break	117%
Peel Strength	>4 lbs/in (18 N/25mm)
Abrasion Resistance	3% Δ Haze

Film Properties (nominal) — not for specification purposes

Glass Type (All 1/4")	Film Type	Reflected (Interior)		9%	12%	Ultra PR S70	Double Tinted							
		Reflected (Exterior)		10%	13%	Ultra PR S70	Double Clear							
		Visible Light Transmitted		68%	41%	Ultra PR S70	Tinted							
Total Solar Energy Rejected	Solar Heat Gain Coefficient (G Value)	btu/h·ft² w/ U Value	Solar Heat Rejected	50%	56%	0.44	0.56	0.42	0.47	2.7	17%	99.9%	23%	0.9
				50%	56%	0.44	0.56	0.47	2.7	20%	99.9%	23%	0.9	
				50%	56%	0.44	0.56	0.47	2.7	20%	99.9%	23%	0.9	
Visible Light to Solar Heat Gain Ratio	Glare Reduction	UV Light Rejected	Solar Heat Reduction	38%	30%	99.9%	23%	1.4						
				38%	30%	99.9%	23%	1.4						
				38%	30%	99.9%	23%	1.4						

Solar Properties — not for specification purposes